





### SILVER 70 C

Silver 70 C films are highly effective at reducing solar heat gain, whilst at the same time continuing to allow most natural light to pass through. Solar glare is greatly diminished and its one-way mirror aspect guarantees privacy from prying eyes, whilst affording a modern feel to the exterior of a building.



SOLAR SCREEN® Warranty

10 YEARS



Fire-resistance rating

**M1** 



Storage from -5°C to +40°C

**3 YEARS** 



European Standard EN 1096-1

**TESTED IN A LABORATORY** 



REACH RoHS compliant RESPECTED



WIDTHS AVAILABLE:

122 cm

152 cm

183 cm

#### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	1 %			
Visible light transmission	30 %			
Reflection of external visible light	44 %			
Reflection of internal visible light	44 %			
Total solar energy rejected	68 %			
Total solar energy rejected 2	64 %			
Solar ratio:				
Solar energy reflection	43 %			
Solar energy absorption	35 %			
Solar energy transmission	22 %			
Reduction in Solar Glare	68 %			
g-value	0.31			
u-value	5.16			
Shading coefficient	0.36			

Installation type	Internal application	
Roll length	30,5 m	
PET / PVC composition	PET	
Thickness	40 μ	

Colour: SILVER MEDIUM

### CONSTRUCTION

- 1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- 2. High optical quality polyester, with anti IR metal particles
- deposit


  3. Bonding adhesive
- **4.** High optical quality polyester
- **5.** PS adhesive, glass polymerization within 15 days
- **6.** Protection release liner, disposable afterinstallation

## INSTALLATION ADVICE

Valid for vertical glazed surfaces and areas not exceeding 2.5 m2

Clear single pane	<b>V</b>
Tinted single pane	<b>V</b>
Reflective tinted single pane	<b>V</b>
Clear double pane	✓
Tinted double pane	!
Reflective tinted double pane	<b>V</b>
Gas-filled double pane - Low E	!
STADIP clear double pane	Į.
STADIP INT. clear double pane	Ī





# MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. sun pose 0808 or 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time.