



SILVER 80 X

Silver 80 X films are highly effective at reducing solar heat gain, whilst at the same time continuing to allow some natural light transmission. This film is particularly well suited for use on glazed roofs, providing effective protection against solar glare whilst its one-way mirror aspect guarantees privacy from prying eyes.



SOLAR SCREEN® Warranty
See the notice "new guarantees for the external films"



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **122 cm**

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

| | |
|--------------------------------------|------|
| Ultraviolet transmission | 1 % |
| Visible light transmission | 18 % |
| Reflection of external visible light | 60 % |
| Reflection of internal visible light | 60 % |
| Total solar energy rejected | 80 % |
| Total solar energy rejected 2 | 85 % |
| Solar ratio : | |
| Solar energy reflection | 55 % |
| Solar energy absorption | 33 % |
| Solar energy transmission | 12 % |
| Reduction in Solar Glare | 83 % |
| g-value | 0.2 |
| u-value | 5.1 |
| Shading coefficient | 0.2 |


Installation type External application

| | |
|-----------------------|--------|
| Roll length | 30,5 m |
| PET / PVC composition | PET |
| Thickness | 40 µ |

Colour : SILVER

CONSTRUCTION

- "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- High optical quality polyester, with anti IR metal particles deposit
- Bonding adhesive
- High optical quality polyester
- PS adhesive, glass polymerization within 15 days
- Protection release liner, disposable after installation



INSTALLATION ADVICE

Valid for vertical glazed surfaces and areas not exceeding 2.5 m²

| | |
|--------------------------------|---|
| Clear single pane | ✓ |
| Tinted single pane | ✓ |
| Reflective tinted single pane | ✓ |
| Clear double pane | ✓ |
| Tinted double pane | ✓ |
| Reflective tinted double pane | ✓ |
| Gas-filled double pane - Low E | ✓ |
| STADIP clear double pane | ✓ |
| STADIP INT. clear double pane | ✓ |

✓ Yes ⚠ Caution ✗ No

MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. sun pose 0808 or 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time.