



WHITE OPAQUE

The White Black Opaqueout film provides comprehensive two-way privacy. Blocking almost all light penetration, this film provides an immediate and effective privacy solution, ideally suited for concealing stock, a storage area, etc.



SOLAR SCREEN® Warranty
10 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant

RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	1 %
Reflection of external visible light	88 %
Reflection of internal visible light	88 %
Total solar energy rejected	86 %

Total solar energy rejected 2 80 %

Solar ratio :	
Solar energy reflection	67 %
Solar energy absorption	27 %
Solar energy transmission	6 %

Reduction in Solar Glare 95 %

g-value 0.13

u-value 5

Shading coefficient 0.1

Installation type Internal application

Roll length 30,5 m


PET / PVC composition PET

Thickness 75 µ

Colour : WHITE

CONSTRUCTION

1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion, with anti IR metal particles deposit
3. Bonding adhesive
4. Dyed polyester without optical distortion
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. sun pose 0808 or 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time.