

DATA JAMMER

Thanks to this polarizing film, create a blackout effect on your LCD or Plasma screens while preserving a perfect view through the glass.



SOLAR SCREEN® Warranty
2 YEARS



Storage from -5°C to +40°C
1 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

122 cm



TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	1%
Visible light transmission.	44%
Reflection of external visible light	8%
Reflection of internal visible light.	9%
Total solar energy rejected.	30%
Total solar energy rejected 2*.	30%
Solar ratio :	
Solar energy reflection.	NC%
Solar energy absorption.	NC%
Solar energy transmission.	NC%
Reduction in Solar Glare.	58%
g-value	NC
u-value	NC
Shading coefficient	NC
Installation type :	
Roll length.	30,5 m
Film composition	PET + PVA
Thickness	132 μ

Colour from the outside :
TRANSPARENT

CONSTRUCTION

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. PVA film
3. PS adhesive, polymerizes with glass within 15 days
4. Polarizing film



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film. Warning: special installation, see installation instruction sheet.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	!

✓ Yes ! Caution ✗ Not recommended
*Recommendations provided on the basis of a glazed surface covering up to 2.5m².